

suprema

# BioEntry W

Outdoor Fingerprint  
IP Reader/Controller

IP65 dust & waterproof  
IK08 vandal-resistant  
Power over Ethernet  
Fingerprint & RFID



**| BioEntry W |** BioEntry Plus/W exquisitely blends benefits of IP access control system with high-level security provided by fingerprint biometrics. Featuring vandal-resistance structure and IP65 rated structure, BioEntry W is ideal for outdoor installation with offering exceptional durability under harsh environment. With its extensive communication interfaces and PoE capability, BioEntry W is truly the ultimate outdoor fingerprint access control device.






# SUPREMA BioEntry W

## Outdoor Fingerprint IP Reader/Controller




### Hardware Features

-  **Worlds Best Fingerprint Recognition Technology**  
- Cutting-edge algorithm ranked top in FVCs and MINEX
-  **IP65 Certified Dust & Water Protection**  
- Ideal for harsh environment and outdoor installation
-  **IK08 Vandal-resistant Structure**  
- Heavy-duty Lexan resin housing with doubled thickness
-  **Ultra Performance**  
- 1:2,000 matches in 1 second
-  **Power over Ethernet**  
- Power supply through a single CAT5/6 wiring
-  **Versatile Interfaces**  
- TCP/IP, RS485, Wiegand, relay
-  **RF Card Options**  
- 13.56MHz Mifare/DesFire

### Secure I/O


- External Relay unit for secure door control and I/O expansion
- Encrypted communication for enhanced security
  - 16MHz 8 bit microprocessor
  - 4 digital inputs and 2 relay outputs
  - Dimension : 143 x 82 x 35 mm (W x H x D)



### Specifications

|                    |   |
|--------------------|---|
| CPU                | 533MHz DSP                                    |
| Memory             | 8MB flash + 8MB RAM                           |
| Fingerprint Sensor | Optical                                       |
| RF Card Option     | 13.56MHz Mifare/DesFire                       |
| Template Capacity  | 10,000 (1:1)                                  |
| Max User           | 5,000   |
| Log Capacity       | 50,000  |
| Ingress Protection | IP65  |
| PoE                | Yes   |
| Interfaces         | TCP/IP, Wiegand, RS485, RS232, TTL I/O, relay |
| Tamper             | Switch  |
| Sound              | 16 bit Hi-Fi voice & sound indication         |
| Operating Temp.    | - 20C ~ 50C                                   |
| Operating Voltage  | 12vDC   |
| Dimensions (mm)    | W50 x H172 x D42                              |
| Certificates       | CE, FCC, KCC, IP65, IK08                      |

### System Configurations



Tele: 513-239-6322 or 866-400-9292  
E-mail: sales@evolvedprotection.com  
Website: www.EvolvedProtection.com

